

LUXORliving R718

Item no.: 4800480

Home and Building control
LUXORliving

Description

- Individual room thermostat LUXORliving
- Setting range 5 - 30°C
- Applications: heating via radiator or underfloor heating, heating and cooling e.g. radiator or cooling ceiling
- Integrated 4-way binary input sensor interface
- Download of the installation software LUXORplug at <https://luxorliving.de/luxorplug>




Technical data

LUXORliving R718	
Operating voltage KNX	Bus voltage, <12 mA
Installation type	Surface-mounted
Display	LED
Interface extension max.	30 m
Ambient temperature	5°C ... 40°C
Measuring range temperature	-5°C ... 45°C

LUXORliving R718	
Setting range temperature	5°C ... 30°C
Contact voltage	5 V Internal provided
Contact current	0.5 mA
Type of protection	IP 20
Protection class	III according to EN 60 730-1

Connection example



Subject to technical changes and misprints

additional information at: www.theben.de/product/4800480



The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

LUXORliving R718

Item no.: 4800480

theben

Scale drawings



Subject to technical changes and misprints

additional information at: www.theben.de/product/4800480

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

31/08/2023

Page 2 of 2