## **DM 4-2 T KNX**


Item no.: 4940280



# Home and Building control KNX

### Description

- 4-way universal dimmer actuator FIX1
- For dimming dimmable LED, incandescent lamps, LV, HV halogen lamps and energy saving lamps
- Also suitable for dimming of dimmable energy-saving lamps
- Also suitable for controlling fans
- LED switching status display for each channel
- Manual operation on device
- Dimming output: 200 W per channel
- Automatic load detection (can be deactivated)
- For R, L and C loads



#### Technical data

	DM 4-2 T KNX
Operating voltage KNX	Bus voltage, ≤10 mA
Operating voltage	230 - 240 V AC 50 - 60 Hz
Frequency	50 – 60 Hz
Stand-by consumption	<1 W
Width	4 modules
Installation type	DIN rail
Type of connection	Terminal screws   Bus connection: KNX bus terminal
Max. cable cross section	Solid wire: 0.5 mm² (Ø 0.8) to 6 mm²   Stranded wire with end sleeve: 0.5   mm² to 4 mm²
Number of channels	4


	DM 4-2 T KNX
Lamp types	Incandescent, low-voltage and high- voltage halogen and dimmable energy saving lamps and LED
Incandescent/halogen lamp load	200 W
LED lamp	Trailing edge (RC-mode): 200 W
Energy saving lamps	Trailing edge (RC-mode): 200 W
Switching capacity min.	2 W
Max. cable length	100 m
Ambient temperature	-5°C 45°C
Type of protection	IP 20
Protection class	II according to EN 60 669

## **DM 4-2 T KNX**

Item no.: 4940280



## Connection example



## Scale drawings

